

ATV/UTV TYRE



KNIGHT



Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
25x8-12	6	6.5	25.0	8.0	340	7
25x10-12	6	8.0	25.0	9.6	420	7
26x9-12	6	7.0	26.0	9.0	410	7
26x11-12	6	9.0	25.8	10.0	480	7
26x12-12	6	8.0	26.0	10.0	520	7
27x9-12	6	7.0	27.0	9.0	440	7
27x11-12	6	7.0	26.9	10.7	495	7
27x12-12	6	9.5	27.0	10.0	550	7
26x11-14	6	8.0	26.0	9.7	465	7
23x8-11	6	6.5	23.5	7.5	290	7
24x9-11	6	7.5	24.3	9.1	365	7



ATLAS



Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
26x8-14	6	6.5	26.0	8.0	355	7
26x9-14	6	7.0	26.0	9.0	395	7
26x10-14	6	8.0	26.0	10.0	430	7
26x11-14	6	9.0	26.0	11.0	465	7
27x9-14	6	7.0	27.0	9.0	410	7
27x11-14	6	9.0	27.0	11.0	480	7

ATV/UTV TYRE



MARS-A



Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
22X11-8	6	9.0	22.3	10.9	395	7
22X10-9	6	8.0	22.0	10.0	365	7
25X12-9	6	9.5	25.2	11.6	495	7
22X11-10	6	9.0	22.2	10.7	385	7
22X8-10	6	7.0	21.9	8.0	275	7
23X8-10	6	6.5	23.4	8.3	300	7
23X10-10	6	8.0	23.4	10.2	375	7
22X7-11	6	5.5	22.0	6.9	245	7
23X8-11	6	6.5	23.4	7.6	290	7
24X8-11	6	6.5	24.0	8.1	320	7
25X8-11	6	6.5	25.1	8.1	355	7
25X10-11	6	8.0	25.2	10.0	430	7
25X8-12	6	6.5	25.2	8.3	340	7
25X10-12	6	8.0	24.4	9.9	420	7
25X12-12	6	9.5	25.0	12.0	480	7
26x9-12	6	7.0	26.0	9.0	410	7
26X10-12	6	8.0	25.9	9.0	440	7
26x11-12	6	9.0	25.8	10.0	480	7
26X12-12	6	9.5	25.9	11.4	520	7
27X10-12	6	8.0	26.9	9.0	490	7
27X12-12	6	9.5	26.9	11.4	550	7
28X10-12	6	8.0	27.8	9.0	450	7



MARS-B



Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
24X8-12	6	6.5	24.5	8.0	310	7
25x12-10	6	9.5	24.8	11.7	495	7
24x11-10	6	9.0	24.0	11.1	440	7
24x9-11	6	7.0	23.8	8.6	365	7
24x10-11	6	8.0	24.2	10.1	395	7

ATV/UTV TYRE

RHEA



Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
25X8-12	6	6.5	25.2	8.2	340	7
25X10-12	6	8.0	25.2	9.5	420	7
26x9-12	6	7.0	25.7	8.8	410	7
26x11-12	6	9.0	25.8	10.0	480	7
27X9-12	6	7.0	27.7	8.5	440	7
27X11-12	6	9.0	27.8	10.6	495	7
26X9-14	6	7.0	26.0	8.5	395	7
26X11-14	6	9.0	26.0	9.7	465	7
27X9-14	6	7.0	26.0	8.5	410	7
27X11-14	6	9.0	26.0	10.0	480	7



OCEANUS



Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
23X8R12	6	6.5	23.0	8.0	280	7
23X10R12	6	8.0	23.1	9.6	365	7
25x8R12	6	6.5	25.0	8.3	340	7
25x8-12	6	6.5	25.0	8.3	340	7
25x10R12	6	8.0	25.0	9.4	420	7
25x10-12	6	8.0	25.0	9.4	420	7
26X10R12	6	8.0	26.0	9.6	440	7
26X12R12	6	9.5	26.0	10.8	520	7
26X9R14	6	7.0	26.2	8.3	395	7
26X11R14	6	9.0	26.2	10.7	465	7
27X9R14	6	7.0	27.0	9.0	410	7
27X11R14	6	9.0	27.0	10.4	480	7

ATV/UTV TYRE

VICTORY

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
25x8-12	6	6.5	24.8	8.0	340	7
25x10-12	6	8.0	25.0	9.9	420	7
26x9-12	6	7.0	26.0	9.0	410	7
26x11-12	6	9.0	25.8	11.0	480	7
26x9-14	6	7.0	26.0	9.0	395	7
26x11-14	6	9.0	26.0	11.0	465	7
27x9-14	6	7.0	27.0	9.0	410	7
27x11-14	6	9.0	27.0	10.8	480	7
28x10-14	6	8.0	28.0	10.0	480	7
29x9-14	6	7.0	29.0	9.0	495	7
29x11-14	6	9.0	29.0	11.0	520	7
30x10-14	6	8.0	30.0	10.0	535	7



STREET



SOFT UNDERGROUND



HARD UNDERGROUND

VENUS

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
23x11-10	6	9.0	23.0	11.0	440	7
24x9-10	6	7.0	24.0	9.0	365	7
24x11-10	6	9.0	24.0	11.0	440	7



STREET



SOFT UNDERGROUND



MUD

ATV/UTV TYRE



VULCAN



Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
25x8-12	6	6.5	24.8	8.0	340	7
25x10-12	6	8.0	25.0	9.9	420	7
26X9-12	6	7.0	26.0	9.0	410	7
26X11-12	6	9.0	25.8	11.0	480	7
27X9-12	6	7.0	27.0	9.0	440	7
27X11-12	6	9.0	26.9	10.7	495	7
28X9-12	6	7.0	27.8	8.8	440	7
28X11-12	6	9.0	27.8	10.8	520	7
27X9-14	6	7.0	27.0	9.0	410	7
27X11-14	6	9.0	27.0	11.0	480	7
28X9-14	6	7.0	27.8	8.8	440	7
28X11-14	6	9.0	27.8	10.8	520	7
30X9-14	6	7.0	29.9	8.8	505	7
30X11-14	6	9.0	29.9	10.7	565	7



EOS



Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
21X7-10	6	5.5	20.6	6.6	235	7
22X7-10	6	5.5	21.4	6.7	255	7
20X10-9	6	8.0	19.9	9.9	300	7
22X10-10	6	8.0	21.7	9.9	355	7

MIDAS



Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
20x11-9	6	9.0	20.0	11.0	340	7
22X11-9	6	9.0	22.0	11.2	395	7
20X11-10	6	9.0	20.0	10.8	330	7
21x7-10	6	5.5	21.3	7.0	235	7
22X7-10	6	5.5	22.0	6.9	255	7
22X11-10	6	9.0	22.4	10.8	385	7
23X7-10	6	5.5	23.0	7.0	275	7

ATV/UTV TYRE



TETHYS



STREET



MIXED
UNDERGROUND



HARD
UNDERGROUND

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
22X10-9	6	8.0	21.9	10.0	365	7
22X7-11	6	5.5	21.9	7.1	245	7
25x8-12	6	6.5	24.8	8.1	340	7
25x10-12	6	8.0	24.9	9.8	420	7



MAXX PLUS



SOFT
UNDERGROUND



MUD



SAND

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity@50MPH(Lbs)	PSI
25x8-12	6	6.5	24.8	7.9	340	7
25X10-12	6	8.0	25.0	9.8	420	7
26X9-12	6	7.0	26.0	8.9	410	7
26X11-12	6	9.0	25.8	10.8	480	7

OUTDOOR POWER EQUIPMENT



LG01

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity (Lbs)	PSI
11x4.00-5	4	3.0	11.3	4.1	330	46
13x5.00-6	4	3.5	13.0	4.3	440	40
13x6.50-6	4	4.5	13.0	6.3	460	28
15x6.00-6	4	4.5	14.9	6.2	570	30
16x6.50-8	4	5.38	15.9	6.6	620	28
18x6.50-8	4	5.38	17.6	6.9	770	28
20x8.00-8	4	7.0	19.4	8.6	950	22

OUTDOOR POWER EQUIPMENT



LG02

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity (Lbs)	PSI
18x8.50-8	4	7.0	17.7	8.0	815	22
18x9.50-8	4	7.0	17.7	8.7	1040	24
20x10.00-8	4	7.0	19.5	9.1	1190	22

LG03

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity (Lbs)	PSI
18x8.50-8	4	7.0	18.0	8.5	815	22
18x8.50-8	6	7.0	18.0	8.5	1000	32



LG04

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity (Lbs)	PSI
11x4.00-5	4	3.0	11.3	4.2	330	46
13x5.00-6	4	3.5	12.9	4.6	440	40
13x6.50-6	4	4.5	13.2	6.4	460	28
15x6.00-6	4	4.5	14.4	5.9	570	30
16x6.50-8	4	5.38	16.0	6.9	620	28
18x8.50-8	4	7.0	17.8	8.2	815	22

OUTDOOR POWER EQUIPMENT



LG05

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity (Lbs)	PSI
4.00-6	2	3.0	13.8	3.9	390	30
3.50-8	2	2.75	15.0	3.5	320	30
4.80/4.00-8	4	3.75	16.0	4.0	670	50

LG06

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity (Lbs)	PSI
4.10/3.50-4	4	3.25	10.6	3.7	350	50
4.10/3.50-5	4	3.25	11.7	3.8	380	50
4.10/3.50-6	4	3.25	12.7	3.8	445	50
4.80/4.00-8	4	3.75	16.2	4.8	670	50



size(inch)

6X1.5
6.7X1.5
7X1.5
7.5X1.75
7.5X2
8X1.75
8X2
8X2.5



size(inch)

9X2
9X2.25
10X1.75
10X2.5
10X2.75
10X3
12X1.75
12X3



size(inch)

8X3.00-4
9X3.50-4
11X4.00-5
13X5.00-6



size(inch)

13X6.50-6
15X6.00-6
15X6.50-8

SEMI SOLID WHEEL

OUTDOOR POWER EQUIPMENT

GF01

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity (Lbs)	PSI
22x11.00-10	4	7.0	23.0	10.0	1000	20
23x10.50-12	4	8.5	22.7	10.4	1000	20

GF02

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity (Lbs)	PSI
205/50-10	4	6.0	18.1	7.8	675	30
215/40-12	4	7.0	18.9	8.0	760	30

OUTDOOR POWER EQUIPMENT



GF03

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity (Lbs)	PSI
22x11.00-10	4	7.0	22.1	10.3	1000	20
23x10.50-12	4	8.5	23.2	9.7	1000	20

GF04

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity (Lbs)	PSI
205/50-10	4	6.0	18.1	7.8	675	30
225/35-12	4	7.0	19.3	8.0	760	30



WAVE

Size	PR	Rim Width	Mounted Diameter	Mounted Width	Max Load Capacity (Lbs)	PSI
23x8.50-12	4	7.0	22.4	8.5	1120	22
23x10.50-12	4	8.5	22.8	10.2	1340	20