

## AGRICULTURAL TIRES R-1 (TT)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
4.00-12	4PR	R-1	535	112	3.00D	240	280
5.00-12	6PR	R-1	590	145	4.00E	200	280
6.00-12	6PR	R-1	635	152	4.50E	250	405
6.00-14	8PR	R-1	690	165	4.50E	250	600
6.00-16	8PR	R-1	690	165	4.50E	250	495
6.50-16	8PR	R-1	765	180	4.50E	250	565
7.50-16	8PR	R-1	810	205	5.50F	210	650
7.50-20	8PR	R-1	910	205	5.50F	240	760
8.3-16	6PR	R-1	790	211	W7	230	695
8.3-20	10PR	R-1	788	211	W7	240	695
8.3-24	6PR	R-1	993	211	W7	240	810
9.5-20	8PR	R-1	950	240	W8	210	955
9.5-24	6PR	R-1	1,048	241	W8	210	940
11.2-24	8PR	QH613	1,103	284	W10	250	1,150
11.2-28	8PR	QH615	1,205	284	W10	250	1,180
11.2-38	6PR	QH611	1,459	284	W10	180	1,150
12.4-24	8PR	QH611/QH666	1,159	315	W11	220	1,285
12.4-24	12PR	QH611/QH666	1,159	315	W11	330	1,600
12.4-28	8PR	QH615	1,260	315	W11	220	1,400
12.4-28	12PR	QH615	1,260	315	W11	330	1,650
12.4-36	8PR	QH666	1,464	315	W11	220	1,500
12.4-36	12PR	QH666	1,464	315	W11	330	1,850
12.4-38	8PR	QH611	1,514	315	W11	220	1,600
12.4-38	12PR	QH611	1,514	315	W11	320	1,850
13.6-24	8PR	QH611	1,210	345	W12	190	1,400
13.6-24	12PR	QH611	1,210	345	W12	260	1,600
13.6-28	8PR	QH611	1,311	345	W12	190	1,500
13.6-28	12PR	QH611	1,311	345	W12	290	1,900
13.6-38	8PR	QH611	1,565	345	W12	210	1,750
13.6-38	12PR	QH611	1,565	345	W12	260	2,000
14.9-24	8PR	QH611/QH666	1,265	378	W13	180	1,600
14.9-24	12PR	QH611/QH666	1,265	378	W13	260	2,000
14.9-26	8PR	QH611	1,316	378	W13	190	1,650
14.9-26	12PR	QH611	1,316	378	W13	260	2,060
14.9-28	8PR	QH612/QH666	1,367	378	W13	180	1,700
14.9-28	12PR	QH612/QH666	1,367	378	W13	250	1,950
15.5-38	10PR	QH611/QH666	1,569	394	W14L	220	2,000
15.5-38	12PR	QH611/QH666	1,569	394	W14L	260	2,120
16.9-24	10PR	QH611	1,333	429	W15L	190	2,000
16.9-24	12PR	QH611	1,333	429	W15L	230	2,120





## AGRICULTURAL TIRES R-1 (TT)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
16.9-28	10PR	QH611	1,435	429	W15L	190	2,120
16.9-28	12PR	QH611	1,435	429	W15L	230	2,360
16.9-30	10PR	QH611/QH666	1,485	429	W15L	190	2,240
16.9-30	12PR	QH611/QH666	1,485	429	W15L	230	2,500
16.9-34	10PR	QH611	1,587	429	W15L	190	2,360
16.9-34	12PR	QH611	1,587	429	W15L	230	2,575
18.4-26	12PR	QH611	1,450	467	DW16	220	2,650
18.4-26	14PR	QH611	1,450	467	DW16	250	2,800
18.4-30	10PR	QH611/QH666	1,552	467	W16L	180	2,500
18.4-30	12PR	QH611/QH666	1,552	467	W16L	220	2,900
18.4-34	10PR	QH611/QH666	1,654	467	W16L	180	2,725
18.4-34	12PR	QH611/QH666	1,654	467	W16L	220	3,000
18.4-38	10PR	QH611/QH666	1,755	467	W16L	180	2,900
18.4-38	12PR	QH611/QH666	1,755	467	W16L	220	3,250
18.4-42	10PR	QH666	1,857	467	W16L	180	3,000
18.4-42	12PR	QH666	1,857	467	W16L	220	3,350
20.8-38	10PR	QH611/QH666	1,834	528	W18L	150	3,150
20.8-38	12PR	QH611/QH666	1,834	528	W18L	190	3,550
23.1-26	12PR	QH611	1,605	587	DW20	170	3,250
23.1-26	16PR	QH611	1,605	587	DW20	220	3,750
23.1-30	12PR	QH611	1,707	587	DW20	170	3,450
23.1-30	16PR	QH611	1,707	587	DW20	225	4,000
24.5-32	12PR	QH666	1,803	622	DW21A	170	4,000
24.5-32	16PR	QH666	1,803	622	DW21A	210	4,500

## IRRIGATION TIRES R-1 (TT/TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
11.2-38 TT	6PR	QH616	1,420	260	W10	180	1,150
11.2-38 TL	6PR	QH616	1,420	260	W10	180	1,150
14.9-24 TT	6PR	QH616	1,265	378	W13	140	1,360
14.9-24 TL	6PR	QH616	1,265	378	W13	140	1,360

R-1 QH612



R-1 QH615



R-1 QH616



## AGRICULTURAL TIRES R-2 (TT)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
12.4-24	8PR	QH651	1,192	315	W11	220	1,285
14.9-24	8PR	QH651	1,305	378	W13	180	1,600
14.9-28	8PR	QH651	1,406	378	W13	180	1,700
18.4-30	10PR	QH651	1,550	467	W16L	180	2,500
18.4-34	10PR	QH651	1,655	467	W16L	180	2,725
18.4-38	10PR	QH651	1,755	467	W16L	180	2,900
23.1-26	12PR	QH651	1,605	587	DW20	170	3,250
23.1-26	16PR	QH651	1,605	587	DW20	220	3,750
23.1-30	12PR	QH651	1,829	610	DW20	170	3,450
23.1-30	16PR	QH651	1,829	610	DW20	225	4,000

## FLOTATION TIRES I-3 (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
400/60-15.5	14PR	QH643	874	400	13.00	360	2,900
400/60-15.5	16PR	QH643	874	400	13.00	400	3,150
500/60-22.5	16PR	QH643	1,172	500	16.00	320	4,875
550/45-22.5	16PR	QH643	1,067	533	16.00	280	4,375
600/50-22.5	16PR	QH643	1,170	610	20.00	260	5,150
600/50-22.5	18PR	QH643	1,170	610	20.00	290	5,800
700/50-26.5	16PR	QH643	1,333	700	24.00	180	5,800
26x12-12	8PR	QH645	648	307	10.50I	140	810
31x15.5-15	8PR	QH645	792	391	13.00	310	1,250
405/70-20	14PR	M880	1,076	407	13.00	350	3,250
405/70-24	14PR	M880	1,178	407	13.00	350	3,250

R-2 QH651



I-3 QH643



I-3 QH645



M880





## INDUSTRIAL TRACTOR F-3 (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
11L-15	10PR	QH631	813	279	8LB	360	1,060
11L-16	12PR	QH631	838	279	8LB	440	1,250
11L-16	12PR	QH632	838	279	8LB	440	1,250
11L-16	12PR	QH633	838	279	8LB	440	1,250

## PADDY TIRES PR-1 (TT)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
6.50-16	6PR	PR-1	813	165	5.00F	250	565
7.50-16	8PR	PR-1	889	203	5.50F	300	750
8.3-20	8PR	PR-1	940	203	W7	270	970
8.3-24	8PR	PR-1	1,041	180	W7	270	1,135
9.5-20	8PR	PR-1	1,050	240	W8	280	955
9.5-24	8PR	PR-1	1,143	230	W8	240	1,315
11.2-20	8PR	PR-1	1,070	340	W10	270	1,518
11.2-24	8PR	PR-1	1,194	280	W10	210	1,465
11-32	10PR	PR-1	1,448	305	W10	160	1,080
12.4-28	8PR	PR-1	1,320	305	W11	200	1,785
13.6-24	10PR	PR-1	1,285	340	W12	280	2,506
13.6-38	10PR	PR-1	1,700	330	W12	230	2,675
14.9-24	8PR	PR-1	1,360	378	W13	180	1,760
14.9-26	10PR	PR-1	1,285	340	W13	260	2,878
14.9-28	10PR	PR-1	1,475	378	W10	230	2,120
14.9-30	10PR	PR-1	1,500	378	W13	230	2,190
16.9-30	10PR	PR-1	1,590	430	W15L	200	2,455
16.9-34	10PR	PR-1	1,651	406	W15L	200	2,605
18.4-30	10PR	PR-1	1,610	450	W16L	230	3,180
18.4-34	10PR	PR-1	1,670	430	W16L	200	3,585
18.4-38	10PR	PR-1	1,810	476	W15L	180	3,165
19.5L-24	12PR	PR-1	1,382	495	W16L	240	3,002
28L-26	14PR	PR-1	1,636	790	DW25	170	4,245

## IMPLEMENT TIRES (TT)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
6.50-16	10PR	QH671	760	165	4.50E	410	1,010
7.00-16	12PR	QH672	790	176	5.50	410	1,335

## FARM TIRES F-2 (TT/TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
4.00-12	4PR	QH621	535	110	3.00D	340	250
4.00-19	4PR	QH621	720	110	3.00D	360	325
5.00-15	4PR	QH621	665	140	4J	300	325
5.00-16	6PR	QH621	665	150	4.00E	390	475
5.50-16	8PR	QH621	710	150	4.00E	370	530
6.00-16	8PR	QH621	740	160	4.00E	450	675
6.50-16	8PR	QH621	750	175	4.50E	420	735
7.5L-15	8PR	QH621	745	208	6LB	330	750
7.50-16	8PR	QH621	810	205	5.50F	390	775
7.50-18	8PR	QH621	860	205	5.50F	390	850
7.50-20	8PR	QH621	910	205	5.50F	370	1,020
9.5L-15	8PR	QH621	780	240	8LB	330	850
11L-15	8PR	QH621	810	280	8LB	300	950
9.00-16	8PR	QH621	890	245	W7L	400	1,200
10.00-16 3RIB/4RIB	10PR	QH621/QH622	910	275	W8L	360	1,120
11.00-16 3RIB/4RIB	10PR	QH621/QH622	970	315	W10L	330	1,320

F-3 QH631

F-3 QH632

F-3 QH633

PR-1

QH671

QH672

F-2 QH621

F-2 QH622







**FI QH642 HIGHWAY**

## IMPLEMENT TIRES I-1 (TT/TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
6.50-16	10PR	QH641	735	173	4.50E	410	920
7.50-16	10PR	QH641	788	211	5.50F	410	1,215
9.00-16	10PR	QH641	848	234	6LB	360	1,500
10.5/80-18	12PR	QH641	885	276	9.0	410	1,550
760L-15	8PR	QH641	734	193	5.5	360	950
9.5L-14	8PR	QH641	741	241	7.0	300	1,090
9.5L-15	8PR	QH641	780	240	8LB	300	1,120
11L-14	8PR	QH641	750	280	8LB	250	1,120
11L-15	12PR	QH641	810	280	8LB	360	1,450
11L-16	8PR	QH641	835	280	8LB	250	1,215
12.5L-15	12PR	QH641	823	318	10.0	360	1,750

## IMPLEMENT TIRES FOR HIGHWAY (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
9.5L-15	12PR	QH642	741	241	7LB	620	1550
11L-15	12PR	QH642	810	280	8LB	620	1800
12.5L-15	12PR	QH642	823	318	10.0	620	2120

## IMPLEMENT TIRES IMP700 (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
10.0/80-12	8PR	IMP700	710	264	9.0	390	1,250
10.0/75-15.3	10PR	IMP700	760	264	9.0	400	1,550
11.5/80-15.3	12PR	IMP700	865	290	9.0	410	2,145
12.5/80-15.3	14PR	IMP700	875	307	9.0	410	2,385
13.0/65-18	14PR	IMP700	890	336	11.0	430	2,575

**I-1 QH641**



**FI QH642**



**IMP700**





## SKID STEER TIRES (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
10-16.5	10PR	SKS-1	779	261	8.25	520	2,135
12-16.5	12PR	SKS-1	830	312	9.75	550	2,865
14-17.5	14PR	SKS-1	922	351	10.50	550	3,875
15-19.5	14PR	SKS-1	1,029	391	11.75	485	4,565
11L-16	12PR	SKS-1	838	279	8.00	440	1,250
10.0/75-15.3	12PR	SKS-1	760	264	9.00	425	1,700
10-16.5	12PR	SKS-2	795	264	8.25	620	2,375
12-16.5	14PR	SKS-2	835	307	9.75	620	3,075
10-16.5	12PR	SKS-3	773	264	8.25	620	2,375
12-16.5	14PR	SKS-3	831	307	9.75	620	3,075
10-16.5	12PR	SKS-4	820	264	8.25	620	2,375
12-16.5	14PR	SKS-4	831	325	9.75	620	3,075
10-16.5	10PR	SKS-5	775	264	8.25	520	2,135
12-16.5	12PR	SKS-5	831	320	9.75	550	2,865
23x8 5-12	6PR	SKS-5	574	213	7.00	340	820
27x8 5-15	6PR	SKS-5	678	213	7.00	340	710
27x10.5-15	6PR	SKS-5	691	259	8.50	340	750
10-16.5	12PR	SKS-6	795	264	8.25	620	2,375
12-16.5	14PR	SKS-6	831	315	9.75	620	3,075
10-16.5	12PR	SKS-7	773	264	8.25	620	2,375
12-16.5	14PR	SKS-7	835	307	9.75	620	3,075
10-16.5	10PR	SKS-8	779	261	8.25	520	2,135
12-16.5	12PR	SKS-8	830	312	9.75	550	2,865

SKS-1



SKS-2



SKS-3



SKS-4



SKS-5



SKS-6



SKS-7



SKS-8





## PNEUMATICS SHAPED SOLID TIRES

## INDUSTRIAL TRACTOR TIRES R-4 (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
10.0/75-15.3	10PR	QH602	760	264	9.0	390	1,525
11.5/80-15.3	12PR	QH602	865	290	9.0	410	2,145
15.5/80-24	12PR	QH602	1,280	378	W13	300	2,900
15.5/80-24	16PR	QH602	1,280	378	W13	400	3,300

## EXCAVATOR TIRES (SET)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
8.25-20	14PR	QH107	992	245	6.50	720	2,240
9.00-20	14PR	QH107	1,030	260	7.00	770	2,575
10.00-20	16PR	QH107	1,062	280	7.50	810	3,000

## FORKLIFT TIRES (SET)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
4.00-8	8PR	QH201	422	108	2.50	960	690
5.00-8	10PR	QH201	469	131	3.00	1,000	1,090
6.00-9	10PR	QH201	540	160	4.00	860	1,505
6.50-10	12PR	QH201	590	178	5.00	970	1,655
7.00-9	10PR	QH201	590	190	5.00	860	1,995
7.00-12	12PR	QH201	676	192	5.00	860	2,060
7.00-15(29x8-15)	12PR	QH201	760	199	5.50	860	2,500
7.50-15	12PR	QH201	798	215	6.00	790	2,600
8.15-15(28x9-15)	14PR	QH201	684	221	7.00	970	3,075
8.25-12	12PR	QH201	728	210	6.50	720	3,060
8.25-15	14PR	QH201	834	236	6.50	720	3,775
10.00-20	16PR	QH202	1,055	278	7.50	790	6,765
12.00-20	20PR	QH202	1,125	315	8.50	965	8,970

QH602

QH107

QH201

QH202



QH301

QH302

QH303

QH304



规格 SIZE	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	单胎负荷 MAX LOADING KG							
					COUNTERBALANCED LIFT TRUCK				OTHER INDUSTRIAL			
					10KM/H		16KM/H		25KM/H		16KM/H	
LOAD	ROTATION	LOAD	ROTATION	LOAD	ROTATION	LOAD	ROTATION					
5.00-8	QH304	469	126	3.00	1,210	970	1,175	880	1,095	820	840	
6.00-9	QH304	545	140	4.00	1,920	1,535	1,855	1,390	1,730	1,295	1,325	
6.50-10	QH304	597	157	5.00	2,640	2,110	2,545	1,910	2,370	1,780	1,820	
7.00-9	QH304	578	170	5.00	2,730	2,015	2,605	1,925	2,530	1,790	1,940	
7.00-12	QH304	683	168	5.00	3,015	2,410	2,910	2,185	2,710	2,035	2,075	
7.00-15	QH303	759	178	5.50	3,590	2,870	3,465	2,600	3,225	2,420	2,475	
8.25-12	QH303	735	206	5.00	3,325	2,660	3,215	2,410	2,995	2,245	2,295	
8.25-15	QH304	847	205	6.50	4,940	3,950	4,765	3,575	4,440	3,330	3,405	
16x8-8	QH304	418	156	4.33	1,500	1,200	1,445	1,085	1,345	1,010	1,035	
18x7-8	QH304	457	165	4.33	2,350	1,880	2,265	1,700	2,110	1,585	1,620	
21x8-9	QH304	535	189	6.00	2,810	2,250	2,715	2,035	2,530	1,895	1,940	
23x9-10	QH304	200	595	6.50	3,420	2,735	3,300	2,475	3,076	2,305	2,355	
27x10-12	QH304	683	236	8.00	4,465	3,570	4,315	3,235	4,020	3,015	3,080	
28x9-15	QH304	700	230	7.00	4,090	3,270	3,945	2,960	3,675	2,755	2,820	
250-15	QH303	734	226	7.00	4,675	3,740	4,515	3,385	4,250	3,155	3,225	

## PRESS ON SOLID TIRES

规格 SIZE	花纹编号 PATTERN	MM	单胎负荷 MAX LOADING KG					
			COUNTERBALANCED LIFT TRUCK			OTHER INDUSTRIAL		
			10KM/H		16KM/H		16KM/H	
LOAD	ROTATION	LOAD	ROTATION	LOAD	ROTATION			
10-5x6 1/2	QH301	254x127x165.1	940	850	910	840	730	
14x4 1/2x8	QH301	356x114x203.2	1,090	965	1,040	960	960	
15 1/2x6x10	QH301/QH302	394x152x254	1,735	1,540	1,660	1,535	1,335	
16x5x10 1/2	QH301/QH302	406x127x266.7	1,400	1,250	1,340	1,240	1,080	
16x6x10 1/2	QH301/QH302	406x152x266.7	1,780	1,580	1,700	1,570	1,370	
16 1/4x5x11 1/4	QH301/QH302	413x127x285.8	1,415	1,260	1,350	1,250	1,090	
16 1/4x6x11 1/4	QH301/QH302	413x152x285.8	1,780	1,580	1,710	1,580	1,370	
18x6x12 1/8	QH301/QH302	457x152x308	1,950	1,740	1,860	1,720	1,500	
18x7x12 1/8	QH301/QH302	457x178x308	2,370	2,110	2,270	2,100	1,820	
18x8x12 1/8	QH301/QH302	457x203x308	2,790	2,480	2,670	2,470	2,150	
21x6x15	QH301/QH302	533x152x381	2,280	2,020	2,160	2,000	1,740	
21x7x15	QH301/QH302	533x178x381	2,670	2,380	2,550	2,360	2,050	
21x8x15	QH301/QH302	533x203x381	3,110	2,795	3,000	2,780	2,420	
22x12x16	QH302	599x305x406.4	5,235	4,660	5,000	4,630	4,030	
22x9x16	QH301/QH302	559x229x406.4	3,750	3,340	3,590	3,320	2,890	
9x5x5	QH301	229x127x127	890	790	850	785	680	





**QH609**

**QH608**



## INDUSTRIAL TRACTOR TIRES R-4 (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
16.9-24	12PR	QH601	1,236	429	DW15	260	3,250
16.9-28	12PR	QH601	1,435	430	DW15	260	3,450
18.4-26	12PR	QH601	1,426	467	DW16A	250	3,875
17.5L-24	12PR	QH601	1,241	445	DW15L	260	3,000
19.5L-24	12PR	QH601	1,314	495	DW17L	230	3,450
21L-24	12PR	QH601	1,402	533	DW18A	220	3,875

## INDUSTRIAL TRACTOR TIRES R-4 (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
19.5L-24	12PR	QH608	1,314	495	DW17L	230	3,455
19.5L-24	12PR	QH608L	1,314	495	DW17L	230	3,455

## INDUSTRIAL TRACTOR TIRES R-4 (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
19.5L-24	12PR	QH609	1,314	495	DW17L	230	3,455

## ALL TRACTION UTILITY TIRES I-3/R-4 (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
10.5/80-18	10PR	QH603	912	274	9.0	370	1,935
12.5/80-18	12PR	QH603	1,001	350	9.0	370	2,625
12.5/80-18	12PR	QH604	1,001	350	9.0	370	2,625

**R-4 QH601**

**R-4 QH603**

**R-4 QH604**





## OTR GRADERS TIRES G-2/L-2 (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
13.00-24	12PR	QH808	1,280	330	8.00TG	300	2,725
13.00-24	16PR	QH808	1,280	330	8.00TG	325	3,075
14.00-24	12PR	QH808	1,350	360	8.00TG	250	3,075
14.00-24	16PR	QH808	1,350	360	8.00TG	350	3,650
15.5-25	12PR	QH808	1,275	395	12.00/1.3	250	2,650
17.5-25	12PR	QH808	1,350	445	14.00/1.5	200	2,900
17.5-25	16PR	QH808	1,350	445	14.00/1.5	280	3,350
17.5-25	20PR	QH808	1,350	445	14.00/1.5	325	3,650
20.5-25	16PR	QH808	1,490	520	17.00/2.0	225	4,000
23.5-25	16PR	QH808	1,815	595	19.00/2.5	200	4,750

## OTR GRADERS TIRES G-2/L-2 (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
15.5-25	12PR	QH807	1,275	395	12.00/1.3	250	2,650
17.5-25	12PR	QH807	1,350	445	14.00/1.5	200	2,900
17.5-25	16PR	QH807	1,350	445	14.00/1.5	280	3,350
17.5-25	20PR	QH807	1,350	445	14.00/1.5	325	3,650
20.5-25	16PR	QH807	1,490	520	17.00/2.0	225	4,000

## OTR GRADERS TIRES G-2/L-2 (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
14.00-24	12PR	QH809	1,350	360	8.00TG	250	3,075
14.00-24	16PR	QH809	1,350	360	8.00TG	350	3,650

G-2/L-2 QH808



G-2/L-2 QH807



G-2/L-2 QH809



QH807

QH809





### OTR TIRES L-3/E-3 (SET/TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
20.5/70-16	14PR	QH811	1,075	410	8.50	285	1,600
14.00-24	16PR	QH811	1,370	375	11.00	375	4,000
14.00-24	24PR	QH811	1,370	375	11.00	575	5,150
15.5-25	12PR	QH811	1,275	395	12.00/1.3	250	3,250
17.5-25	16PR	QH811	1,350	445	14.00/1.5	475	7,300
20.5-25	20PR	QH811	1,490	520	17.00/2.0	450	9,500
23.5-25	20PR	QH811	1,615	595	19.00/2.5	375	10,900
26.5-25	28PR	QH811	1,743	645	22.00/3.0	475	15,500
29.5-25	28PR	QH811	1,850	750	25.00/3.5	425	17,500
16.00-24	20PR	QH811	1,490	430	11.25/2.0	400	5,450
16.00-25	24PR	QH811	1,490	430	11.25/2.0	750	11,500
16.00-25	28PR	QH811	1,490	430	11.25/2.0	875	12,700
18.00-25	32PR	QH811	1,615	495	13.00/2.5	850	16,000
16/70-20	16PR	QH811	1,067	410	13.00	350	2,900
16/70-24	16PR	QH811	1,175	410	13.00	350	3,350

### OTR TIRES L-3/E-3 (SET/TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
17.5-25	16PR	QH812	1,350	445	14.00/1.5	475	7,300
20.5-25	20PR	QH812	1,490	520	17.00/2.0	450	9,500
23.5-25	20PR	QH812	1,615	595	19.00/2.5	375	10,900
26.5-25	28PR	QH812	1,743	645	22.00/3.0	475	15,500

### OTR TIRES L-5 (SET/TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX LOADING KG
17.5-25	16PR	L5	1,340	420	14.00/1.5	475	7,300
20.5-25	20PR	L5	1,479	500	17.00/2.0	450	9,500
23.5-25	20PR	L5	1,588	568	19.00/2.5	375	10,900
26.5-25	28PR	L5	1,758	643	22.00/3.0	475	15,500
29.5-25	28PR	L5	1,868	718	25.00/3.5	425	17,500

L-3/E-3 QH811

L-3/E-3 QH812

L-5



QH100

QH101





## BIAS TRAILER TIRES (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE PSI	单胎负荷 MAX LOADING LBS
ST175/80D13	6PR	QH500	610	177	5.00	50	1,360
ST205/75D14	6PR	QH500	664	203	5.50	50	1,760
ST205/75D15	6PR	QH500	689	203	5.50	50	1,820
ST225/75D15	8PR	QH500	719	223	6.00	65	2,540

## BIAS TRAILER TIRES (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE PSI	单胎负荷 MAX LOADING LBS
ST175/80D13	6PR	QH501	610	177	5.00	50	1,360
ST205/75D14	6PR	QH501	664	203	5.50	50	1,760
ST205/75D15	6PR	QH501	689	203	5.50	50	1,820
ST225/75D15	8PR	QH501	719	223	6.00	65	2,540

## BIAS TRAILER TIRES (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE PSI	单胎负荷 MAX LOADING LBS
ST235/80D16	10PR	QH506	782	235	6.50	80	3,640

## BIAS TRAILER TIRES (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE PSI	单胎负荷 MAX LOADING LBS
7.50-16	10PR	QH504	808	220	6.00	75	2,760

## BIAS TRAILER TIRES (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE PSI	单胎负荷 MAX LOADING LBS
7.00-15	10PR	QH505	752	202	5.50	80	2,340
7.50-16	10PR	QH505	808	220	6.00	75	2,760
ST205/90D15	10PR	QH505	752	202	5.50	80	2,340
ST225/90D16	10PR	QH505	808	220	6.00	75	2,760

## RADIAL TRAILER TIRES (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE PSI	单胎负荷 MAX LOADING LBS
ST175/80R13	6PR	QH100/QH101	610	177	5.00	50	1,360
ST205/75R14	6PR	QH100/QH101	664	203	5.50	50	1,760
ST205/75R15	6PR	QH100/QH101	689	203	5.50	50	1,820
ST205/75R15	8PR	QH100/QH101	689	203	5.50	65	2,150
ST225/75R15	8PR	QH100/QH101	719	223	6.00	65	3,540
ST225/75R15	10PR	QH100/QH101	719	223	6.00	80	3,830
ST235/80R16	10PR	QH100/QH101	782	235	6.50	80	3,520

QH500



QH501



QH506



QH504



QH505



QH100



QH101





## BIAS MOBILE HOME TIRES (SET)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE PSI	单胎负荷 MAX LOADING LBS
6.00-9	8PR	QH401	515	150	4.00	85	1,375

## BIAS MOBILE HOME TIRES (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE PSI	单胎负荷 MAX LOADING LBS
8-14.5	14PR	QH400	707	203	6.00	115	3,040

## BIAS TRUCK TIRES

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE PSI	单胎负荷 MAX LOADING LBS
10.00-20 TTF	14PR	RG037	1,055	254	7.50	90	5,730
11-22.5 TL	14PR	RG036 / RG038	1,054	279	8.25	100	6,175

QH401

QH400



RG036

RG037

RG038



## BIAS BOAT TRAILER TIRES (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE PSI	单胎负荷 MAX LOADING LBS
4.80-8	4PR	QH502	423	121	3.75	60	585
4.80-8	6PR	QH502	423	121	3.75	90	760
5.70-8	4PR	QH502	469	146	4.50	50	715
5.70-8	6PR	QH502	469	146	4.50	75	910
5.70-8	8PR	QH502	469	146	4.50	100	1,070
4.80-12	4PR	QH502	524	121	3.75	60	785
4.80-12	6PR	QH502	524	121	3.75	90	990
5.30-12	4PR	QH502	548	135	4.25	55	855
5.30-12	6PR	QH502	548	135	4.25	80	1,050
5.30-12	8PR	QH502	548	135	4.25	90	1,140

## BIAS BOAT TRAILER TIRES (TL)

规格 SIZE	层级 PLY	花纹编号 PATTERN	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准轮辋 STANDARD RIM	标准气压 RELEVANT PRESSURE PSI	单胎负荷 MAX LOADING LBS
16.5x6.5-8	4PR	QH503	411	165	5.375	45	615
16.5x6.5-8	6PR	QH503	411	165	5.375	70	785
16.5x6.5-8	8PR	QH503	411	165	5.375	90	910
18.5x8.5-8	4PR	QH503	462	213	7.00	35	760
18.5x8.5-8	6PR	QH503	462	213	7.00	50	935
18.5x8.5-8	8PR	QH503	462	213	7.00	70	990
20.5x8.0-10	4PR	QH503	518	203	6.00	35	910
20.5x8.0-10	6PR	QH503	518	203	6.00	50	1,100
20.5x8.0-10	8PR	QH503	518	203	6.00	70	1,320
20.5x8.0-10	10PR	QH503	518	203	6.00	90	1,520

QH502

QH503

